

Mercury
S-Series

5
Years

*Guarantee on
Inner Tank

Mercury
F-Series

10
Years

*Guarantee on
Inner Tank



IS:16544

CM/L-6200196909



IS:16544

CM/L-6200196909

 **VENUS**TM
Hot Water Professionals

*Let the Sunshine Meet
Your Shower Time*

IS:16544

CM/L-6200196909

15
Years

*Guarantee on
Inner Tank



Mercury
E-Series

 **VENUS**TM
Hot Water Professionals

VENUS HOME APPLIANCES (P) LTD.

CENTRAL MARKETING OFFICE: No.18, 1st Link Street, Nehru
Nagar, Kottivakkam, Chennai - 600041. Ph - 044 - 3554 6900.
Customer Care: 08144666999 Whatsapp: 09884064999



P/N - 10 / 2025

VENUS SOLAR WATER HEATER

Venus has been at the forefront of the water heater business for over 60 years now. With a wide range of models that has given warmth to millions of families across India, constant innovation has been the key. Among many innovations one of the key innovation is a Solar water heater that uses solar power which helps people save money on their power bills. Also our unique product is energy efficient-using Vacuum tube technology and Insulated tanks.

Mercury E-Series

Product Specifications**

Description	MY100E	MY150E	MY200E				
Capacity	100 Liters per day	150 Liters per day	200 Liters per day				
No. of Vacuum Tubes	10 Nos	15 Nos	20 Nos				
Pipe Connection	1"	1"	1"				
Backup Electric Heating (Optional at extra cost)	2 kw heating element	2 kw heating element	2 kw heating element				
PUF Insulation Thickness	5cm	5cm	5cm				
Stand Angle	24°	24°	24°				
Daily Usage	upto 4 persons	upto 6 persons	upto 8 persons				
Guarantee on Inner Tank	15 Years*	15 Years*	15 Years*				
Guarantee on Product	10 Years*	10 Years*	10 Years*				
Maximum No. of Outlets	2	3	4				
Dimension (in mm)							
Model	A	B	C	D	E	F	G
MY100E	1210	1850	1740	480	820	1130	750
MY150E	1210	1850	1740	480	1220	1530	750
MY200E	1210	1850	1740	480	1620	1930	750

*Refer "Terms & Conditions" in User Manual / Technical data sheet.

**Specifications subject to change without prior notice

Mercury S-Series

Product Specifications**

Description	MY100S	MY150S	MY200S				
Capacity	100 Liters per day	150 Liters per day	200 Liters per day				
No. of Vacuum Tubes	10 Nos	15 Nos	20 Nos				
Pipe Connection	3/4"	3/4"	3/4"				
Backup Electric Heating (Optional at extra cost)	2 kw heating element	2 kw heating element	2 kw heating element				
PUF Insulation Thickness	5cm	5cm	5cm				
Stand Angle	24°	24°	24°				
Daily Usage	upto 4 persons	upto 6 persons	upto 8 person				
Guarantee on Inner Tank	5 Years*	5 Years*	5 Years*				
Guarantee on Product	5 Years*	5 Years*	5 Years*				
Maximum No. of Outlets	2	3	4				
Dimension (in mm)							
Model	A	B	C	D	E	F	G
MY100S	1210	1850	1740	480	820	1130	750
MY150S	1210	1850	1740	480	1220	1530	750
MY200S	1210	1850	1740	480	1620	1930	750


*Refer "Terms & Conditions" in User Manual / Technical data sheet.

**Specifications subject to change without prior notice

Features



Fusion Blue line coating technology (F-series)



Crystal Blue Glassline with Titanium (E-series)



Superior corrosion resistant SS304 Inner tank (S-series)



5cm Thick PUF Insulation for minimum heat loss



Long life corrosion proof Pre coated outer cladding



Backup electric heating element for cold rainy days



Exclusive Venus Vacuum Tube Technology with triple layer coating for maximum absorption of solar Energy



Powder coated GI / SS201 stand - sturdy and rust resistant

Mercury F-Series


Product Specifications**

Description	MY100F	MY150F	MY200F				
Capacity	100 Liters per day	150 Liters per day	200 Liters per day				
No. of Vacuum Tubes	10 Nos	15 Nos	20 Nos				
Pipe Connection	3/4"	3/4"	3/4"				
Backup Electric Heating (Optional at extra cost)	2 kw heating element	2 kw heating element	2 kw heating element				
PUF Insulation Thickness	5cm	5cm	5cm				
Stand Angle	24°	24°	24°				
Daily Usage	upto 4 persons	upto 6 persons	upto 8 person				
Guarantee on Inner Tank	10 Years*	10 Years*	10 Years*				
Guarantee on Product	5 Years*	5 Years*	5 Years*				
Maximum No. of Outlets	2	3	4				
Dimension (in mm)							
Model	A	B	C	D	E	F	G
MY100F	1210	1850	1740	480	820	1130	750
MY150F	1210	1850	1740	480	1220	1530	750
MY200F	1210	1850	1740	480	1620	1930	750

*Refer "Terms & Conditions" in User Manual / Technical data sheet.

**Specifications subject to change without prior notice

Front View



Side View

